



**Kömmerling®**

TODAY FOR TOMORROW



OPEN FOR YOUR HOME DECORATING IDEAS

**Kömmerling PremiSlide 76**

# PERFECT FUNCTIONALITY FOR DREAMLIKE VIEWS

## The sliding system with comfort

Kömmerling PremiSlide 76 opens up all kinds of possibilities for harmoniously integrating windows and doors into the facade. The sliding system is impressive with outstanding performance and progressive properties.

Whether with a PVC-U casement or a combined outer frame made of PVC-U and aluminium, Kömmerling PremiSlide 76 can be manufactured in both variants. With its construction depth of 76 millimetres, the sliding system proves itself not only in homes, but also in public buildings such as schools or offices. ECO SLIDE, the user-friendly sliding fitting from our cooperation partner Siegenia, ensures perfect functionality. Kömmerling PremiSlide 76 also sets new standards in terms of sustainability: Thanks to excellent insulation, the system achieves the best energy saving value in its product class.

### > HIGH THERMAL INSULATION VALUE

Excellent energy saving properties: Even in the standard version, Kömmerling PremiSlide 76 achieves a  $U_f$  value of up to  $1.4 \text{ W}/(\text{m}^2\text{K})$ .

### > STABLE GLAZING

Triple glazing with a thickness of up to 50 mm.

### > FUNCTIONALITY

The maximum dimensioned steel reinforcements and the welded corner connectors ensure functional reliability and high statics.

### > ELEGANT DESIGN

In both the fixed and sliding parts, Kömmerling PremiSlide 76 is characterised by a slender profile sight line.

### > INNOVATIVE TECHNOLOGY

The design is based on the Kömmerling 76 double seal system, combined with the user-friendly and nonwearing ECO SLIDE hardware system.

### > EFFECTIVE VENTILATION

The ECO SLIDE carriage provides the basis for individual gap ventilation.

> Space-saving opening

> Large glazed areas

> Wide design spectrum

> Effective ventilation

$U_w$  value  
up to  
**0.70**  
 $\text{W}/(\text{m}^2\text{K})$





# EASY OPERATION THANKS TO CLEVER TECHNOLOGY

ECO SLIDE the high-quality sliding fitting from Siegenia

Easy to open, damped braking, smooth closing – that's how Kömmerling PremiSlide 76 works thanks to the smooth-running carriages of the sliding hardware ECO SLIDE. This is because these absorb the stopping movement of the sashes by means of a sideways movement, providing a gliding guide. Shortly before reaching the end position, the sash is braked by the SOFT CLOSE damper and then pulled into the closed position as if by itself. This not only protects the sliding elements, but also protects small and large hands from injury.



- > **Versatile:**  
For practical sliding windows and lightweight sliding doors
- > **User-friendly operation:** For a smooth and nonwearing locking movement
- > **Can be combined with the SOFT CLOSE damper:** For smooth sliding into the fastening position







# COLOUR AND DESIGN HOWEVER YOU WANT

Classic PVC-U white or striking plain tones? Exclusive metallic colours or wood look? Or how about AluClip, the variant with a sophisticated aluminium cladding? Kömmerling PremiSlide 76 offers you a wide range of design options.



Kömmerling PremiSlide 76  
Standard laminated with  
PVC-U frame



Kömmerling PremiSlide 76  
AluClip with PVC-U frame



Kömmerling PremiSlide 76  
Standard laminated with  
combined outer frame  
made of PVC-U and aluminium



Kömmerling PremiSlide 76  
AluClip with combined  
outer frame made of PVC-U  
and aluminium

# #KömmerlingForTomorrow

profine GmbH  
**Kömmerling**

Zweibrücker Straße 200  
66954 Pirmasens  
Tel. +49 (0) 6331 560  
E-mail: [info@koemmerling.com](mailto:info@koemmerling.com)

[www.koemmerling.com](http://www.koemmerling.com)

